



300 AAC Blackout

.308"	30
	Spitzer SP Hot-
	Cor®
Weight (grains)	200
Ballistic Coefficient	0.478
Sectional Density	0.301
COAL Tested	2.160"
Speer Part No.	2211

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 1680	Lake City	Federal 205	11.9	934	13.4	1111
Accurate 5744	Lake City	Federal 205	10.8	958	12.1	1110
Alliant Power Pro 1200-R	Lake City	Federal 205	12.1	947	13.7 C	1109
Alliant Reloder 10X	Lake City	Federal 205	12.7	960	13.9 C	1101
Vihtavuori N120	Lake City	Federal 205	11.0	993	11.8	1096
Accurate LT-30	Lake City	Federal 205	12.3	941	13.5 C	1091
IMR 4227	Lake City	Federal 205	10.2	952	11.0	1088
Alliant Reloder 7	Lake City	Federal 205	12.1	940	12.9	1088
IMR 4198	Lake City	Federal 205	11.4	942	12.3	1080

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load