



300 Holland & Holland Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	3.500"	3.500"	3.355"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	67.0	2807	74.0	3136
IMR 4831	Winchester	CCI 200	67.0	2952	71.0	3134
IMR 4350	Winchester	CCI 200	65.0	2947	69.0	3134
Alliant Reloder 23	Federal	Federal 215	65.9	2811	72.8	3077
Alliant Power Pro 4000-MR	Federal	Federal 215	63.2	2796	70.1	3074
Alliant Reloder 17	Federal	Federal 215	60.2	2830	66.2	3053
Alliant Reloder 16	Federal	Federal 215	60.2	2787	66.4	3048
Alliant Reloder 19	Winchester	CCI 200	63.0	2835	67.0	3002
IMR 4064	Winchester	CCI 200	56.0	2799	60.0	2990
Winchester 760	Winchester	CCI 250	63.0	2741	67.0	2979
Accurate 4350	Winchester	CCI 250	61.0	2731	65.0	2898
Vihtavuori N165	Winchester	CCI 200	63.0	2714	67.0	2881
Accurate 3100	Winchester	CCI 250	64.0	2694	68.0	2869
IMR 4895	Winchester	CCI 200	52.0	3550	56.0	2841
IMR 3031	Winchester	CCI 200	52.0	2598	56.0	2833
Accurate 2700	Winchester	CCI 250	54.0	2628	58.0	2778
IMR 4320	Winchester	CCI 200	51.0	2518	55.0	2759
IMR SR 4759 (reduced load)	Winchester	CCI 200	24.0	1642	28.0	1901

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load