



## 300 Remington Short Action Ultra Magnum

0.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	2.800"	2.800"	2.685"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N560	Remington	CCI 200	67.0	2886	71.0 C	3063
Winchester 760	Remington	CCI 250	62.0	2860	66.0	3035
IMR 4831	Remington	CCI 200	63.0	2808	67.0 C	3011
Alliant Reloder 22	Remington	CCI 200	66.0	2839	70.0 C	3006
Alliant Reloder 19	Remington	CCI 200	65.0	2807	69.0 C	2999
Hodgdon H4350	Remington	CCI 200	60.0	2809	64.0	2983
IMR 4350	Remington	CCI 200	60.5	2784	64.5	2978
IMR 7828	Remington	CCI 200	67.0	2834	69.0 C	2928

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*