



## 300 Savage

<b>.308"</b>	<b>30</b>
<b>Weight (grains)</b>	<b>TNT® HP</b>
<b>Ballistic Coefficient</b>	125
<b>Sectional Density</b>	0.341
<b>COAL Tested</b>	0.188
<b>Speer Part No.</b>	2.580"
	1986

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2460	Federal	CCI 250	40.0	2644	<b>44.0 C</b>	2987
Vihtavuori N140	Federal	CCI 200	42.0	2624	<b>46.0 C</b>	2946
IMR 4895	Federal	CCI 200	40.0	2601	<b>44.0 C</b>	2887
Hodgdon BL-C(2)	Federal	CCI 250	36.0	2583	<b>40.0 C</b>	2884
Winchester 748	Federal	CCI 250	43.0	2545	<b>47.0 C</b>	2858
IMR 4320	Federal	CCI 200	41.0	2490	<b>45.0 C</b>	2829
IMR 3031	Federal	CCI 200	38.0	2548	<b>42.0 C</b>	2796
IMR 4064	Federal	CCI 200	39.0	2453	<b>43.0 C</b>	2707
Hodgdon H380	Federal	CCI 250	44.0	2324	<b>48.0 C</b>	2626
Hodgdon H414	Federal	CCI 250	43.0	2272	<b>47.0 C</b>	2537
IMR 4350	Federal	CCI 200	41.0	2201	<b>45.0 C</b>	2443

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*