



300 Weatherby Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN	30 Match BTHP
Weight (grains)	165	165	165	168
Ballistic Coefficient	0.520	0.444	0.354	0.534
Sectional Density	0.248	0.248	0.248	0.253
COAL Tested	3.560"	3.560"	3.495"	3.560"
Speer Part No.	2034	2035	2038	2040

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 25	Remington	CCI 250	85.0	3054	89.0 C	3204
Hodgdon H1000	Remington	CCI 250	84.0	3007	88.0	3184
Vihtavuori N165	Remington	CCI 250	82.0	2921	86.0	3160
Alliant Reloder 22	Remington	CCI 250	79.0	2964	83.0	3119
Accurate 3100	Remington	CCI 250	76.0	2923	80.0	3112
Hodgdon H4831SC	Remington	CCI 250	78.0	2939	82.0	3110
Alliant Reloder 19	Remington	CCI 250	76.0	2898	80.0	3105
IMR 4831	Remington	CCI 250	74.0	2914	78.0	3092
IMR 7828	Remington	CCI 250	78.0	2844	82.0	3050
Hodgdon H414	Remington	CCI 250	70.0	2905	74.0	3042
Hodgdon H4350	Remington	CCI 250	71.0	2799	75.0	3011
Accurate 4350	Remington	CCI 250	70.0	2767	74.0	2982
Winchester 760	Remington	CCI 250	70.0	2819	74.0	2946
IMR 4350	Remington	CCI 250	70.0	2726	74.0	2941

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load