



300 Winchester Magnum

.308"	30
	Plinker® SPRN
Weight (grains)	100
Ballistic Coefficient	0.144
Sectional Density	0.151
COAL Tested	2.960"
Speer Part No.	1805

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 15	Winchester	CCI 250	68.0	3352	72.0	3604
Hodgdon H322	Winchester	CCI 250	61.0	3339	65.0	3552
Vihtavuori N135	Winchester	CCI 250	65.0	3330	69.0	3543
Accurate 2520	Winchester	CCI 250	64.0	3253	68.0	3479
IMR 4064	Winchester	CCI 250	65.0	3233	69.0	3421
Hodgdon H380	Winchester	CCI 250	70.0	3095	74.0	3396
IMR 4895	Winchester	CCI 250	62.0	3161	66.0	3381
IMR 4320	Winchester	CCI 250	64.0	3095	68.0	3258
IMR SR 4759 (reduced load)	Winchester	CCI 250	21.0	1801	23.0	1975

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load