



## 300 Winchester Magnum

.308"	30 HP
Weight (grains)	130
Ballistic Coefficient	0.244
Sectional Density	0.196
COAL Tested	3.260"
Speer Part No.	2005

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	74.6	3035	<b>82.8</b>	3478
Vihtavuori N160	Winchester	CCI 250	76.0	3222	<b>80.0</b>	3465
Alliant Reloder 16	Federal	Federal 215	69.2	3144	<b>76.6</b>	3445
Alliant Reloder 23	Federal	Federal 215	73.2	3104	<b>81.4 C</b>	3428
Alliant Power Pro 4000-MR	Federal	Federal 215	68.2	3044	<b>75.5</b>	3400
Alliant Reloder 17	Federal	Federal 215	66.8	3164	<b>71.9</b>	3387
Hodgdon H4350	Winchester	CCI 250	74.0	3165	<b>78.0 C</b>	3385
IMR 4831	Winchester	CCI 250	76.0	3193	<b>80.0</b>	3379
Accurate 3100	Winchester	CCI 250	78.0	3161	<b>82.0 C</b>	3363
IMR 4350	Winchester	CCI 250	73.0	3175	<b>77.0</b>	3342
Hodgdon H4831SC	Winchester	CCI 250	78.0	3110	<b>82.0 C</b>	3291
IMR 7977	Federal	Federal 215	76.4	2928	<b>84.8 C</b>	3254
Alliant Reloder 15	Winchester	CCI 250	63.0	3016	<b>67.0</b>	3243
Hodgdon H380	Winchester	CCI 250	68.0	3052	<b>72.0</b>	3213
IMR 4064	Winchester	CCI 250	62.0	2984	<b>66.0</b>	3174
IMR 3031	Winchester	CCI 250	57.0	2882	<b>61.0</b>	3050
IMR 4320	Winchester	CCI 250	53.0	2574	<b>57.0</b>	2738

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*