



300 Winchester Magnum

.308"	30 SPFN Hot-Cor®	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	150	150	150	150
Ballistic Coefficient	0.295	0.417	0.377	0.295
Sectional Density	0.226	0.226	0.226	0.226
COAL Tested	3.130"	3.330"	3.330"	3.285"
Speer Part No.	2011	2022	2023	2026

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	75.1	3059	83.0 C	3395
Alliant Power Pro 4000-MR	Federal	Federal 215	70.4	3033	78.1	3328
Alliant Reloder 16	Federal	Federal 215	67.7	3032	75.2	3318
Alliant Reloder 17	Federal	Federal 215	67.7	3046	74.9	3308
Alliant Reloder 19	Winchester	CCI 250	74.0	3086	78.0 C	3301
Alliant Reloder 23	Federal	Federal 215	71.5	2934	79.0 C	3228
Alliant Reloder 22	Winchester	CCI 250	76.0	3001	80.0 C	3227
Accurate 3100	Winchester	CCI 250	76.0	3064	80.0 C	3225
Hodgdon H4350	Winchester	CCI 250	72.0	3026	76.0 C	3219
Vihtavuori N160	Winchester	CCI 250	72.0	2975	76.0	3199
Hodgdon H4831SC	Winchester	CCI 250	76.0	2982	80.0 C	3156
IMR 4831	Winchester	CCI 250	72.0	2915	76.0	3118
IMR 4350	Winchester	CCI 250	69.0	2918	73.0	3091
Winchester 760	Winchester	CCI 250	64.0	2932	68.0	3086
Hodgdon H414	Winchester	CCI 250	65.0	2902	69.0	3071
Hodgdon H380	Winchester	CCI 250	65.0	2855	69.0	3070
Accurate 2700	Winchester	CCI 250	65.0	2881	69.0	3065
Hodgdon H1000	Winchester	CCI 250	80.0	2910	84.0 C	3063
Alliant Reloder 15	Winchester	CCI 250	60.0	3058	64.0	3058
IMR SR 4759 (reduced load)	Winchester	CCI 250	26.0	1884	28.0	2028

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load