



300 Winchester Short Magnum

.308"	30 HP
Weight (grains)	130
Ballistic Coefficient	0.244
Sectional Density	0.196
COAL Tested	2.730"
Speer Part No.	2005

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Federal	Federal 215	66.0	3205	73.2 C	3548
Winchester 760	Winchester	CCI 250	72.0	3353	76.0	3533
Hodgdon H414	Winchester	CCI 250	70.0	3345	74.0	3523
IMR 4064	Winchester	CCI 200	63.0	3325	67.0	3505
Vihtavuori N540	Winchester	CCI 200	64.0	3314	68.0	3498
Alliant Reloder 17	Federal	Federal 215	64.7	3134	71.6	3489
IMR 4350	Winchester	CCI 200	71.0	3277	75.0 C	3476
Hodgdon Varget	Winchester	CCI 200	64.0	3269	68.0	3468
Hodgdon 4350	Federal	Federal 215	66.5	3189	73.7	3466
Alliant Reloder 15	Winchester	CCI 200	63.0	3285	67.0	3459
Accurate 4350	Federal	Federal 215	68.0	3127	74.7 C	3457
Alliant Power Pro 2000-MR	Federal	Federal 215	62.2	3177	67.9	3439
Hodgdon H380	Winchester	CCI 200	68.0	3272	72.0	3437
Accurate 5744 (reduced load)	Winchester	CCI 200	29.0	2113	31.0	2227

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load