



300 Winchester Short Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	2.800"	2.780"	2.760"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	61.8	2757	68.3 C	3022
Alliant Reloder 19	Winchester	CCI 200	64.5	2819	68.5 C	2978
IMR 4831	Winchester	CCI 200	63.0	2820	67.0 C	2970
Alliant Reloder 22	Winchester	CCI 200	64.5	2797	68.5 C	2958
Alliant Power Pro 4000-MR	Federal	Federal 215	57.5	2661	63.8	2948
IMR 7828	Winchester	CCI 200	66.0	2805	70.0 C	2947
IMR 4350	Winchester	CCI 200	61.0	2782	65.0	2946
Alliant Reloder 23	Federal	Federal 215	59.5	2694	65.9 C	2945
Winchester 760	Winchester	CCI 250	61.0	2786	65.0	2941
Hodgdon H414	Winchester	CCI 250	60.0	2786	64.0	2939
Alliant Reloder 17	Federal	Federal 215	55.5	2697	61.6	2934
Hodgdon H4350	Winchester	CCI 200	59.5	2745	63.5	2920
Alliant Reloder 16	Federal	Federal 215	55.5	2689	61.6 C	2913
Hodgdon H4831SC	Winchester	CCI 200	65.0	2780	69.0 C	2906
Accurate 2700	Winchester	CCI 250	58.0	2750	62.0	2896
Vihavuori N160	Winchester	CCI 200	61.0	2732	65.0	2867
Hodgdon H380	Winchester	CCI 250	58.0	2705	62.0	2843

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load