



308 Norma Magnum

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	180	180	180
Ballistic Coefficient	0.545	0.441	0.374
Sectional Density	0.271	0.271	0.271
COAL Tested	3.345"	3.345"	3.225"
Speer Part No.	2052	2053	2063

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4831	Norma	CCI 250	67.0	2763	71.0	3000
Hodgdon H380	Norma	CCI 250	59.0	2644	63.0	2888
Accurate 3100	Norma	CCI 250	63.0	2645	67.0	2847
IMR 7828	Norma	CCI 250	68.0	2666	72.0	2830
IMR 4064	Norma	CCI 250	54.0	2560	58.0	2805
IMR 4320	Norma	CCI 250	55.0	2562	59.0	2797
Winchester 760	Norma	CCI 250	59.0	2512	63.0	2728
IMR 4198 (reduced load)	Norma	CCI 250	29.0	1798	31.0	1916

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load