



308 Winchester

.308"	30
Weight (grains)	Varminter HP
Ballistic Coefficient	110
Sectional Density	0.028
COAL Tested	0.166
Speer Part No.	2.405"
	1835

NOTE: These loads held to under 2900 fps due to bullet construction.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4895	IMI Commercial	CCI 200	39.0	2642	43.0	2908
IMR 4064	IMI Commercial	CCI 200	41.5	2644	45.5	2899
Hodgdon H380	IMI Commercial	CCI 250	47.0	2670	51.0 C	2894
IMR 3031	IMI Commercial	CCI 200	38.5	2619	42.5	2893
Winchester 748	IMI Commercial	CCI 250	42.0	2639	46.0	2887
IMR 4198	IMI Commercial	CCI 200	32.0	2561	36.0	2875
Hodgdon H322	IMI Commercial	CCI 200	37.0	2521	41.0	2830
Alliant Reloder 7	IMI Commercial	CCI 200	33.0	2481	37.0	2823
IMR 4227	IMI Commercial	CCI 200	25.0	2135	29.0	2494

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load