



308 Winchester

.308"	30 Spitzer BTSP	30 Spitzer SP Hot-Cor®	30 Grand Slam® SP/CANN
Weight (grains)	165	165	165
Ballistic Coefficient	0.520	0.444	0.354
Sectional Density	0.248	0.248	0.248
COAL Tested	2.800"	2.800"	2.685"
Speer Part No.	2034	2035	2038

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	45.7	2646	50.3 C	2857
Alliant Reloder 15	IMI Commercial	CCI 200	43.0	2616	47.0 C	2849
Accurate 2520	IMI Commercial	CCI 250	41.0	2527	45.0	2783
Vihtavuori N140	IMI Commercial	CCI 200	42.0	2551	46.0 C	2779
Accurate 2460	IMI Commercial	CCI 250	40.0	2489	44.0	2772
Hogdon CFE 223	Federal	Federal 210	41.8	2560	46.2	2768
IMR 4064	IMI Commercial	CCI 200	41.0	2507	45.0	2761
IMR 3031	IMI Commercial	CCI 200	39.0	2507	43.0	2759
Alliant AR-Comp	Federal	Federal 210	38.7	2518	43.0	2750
Winchester 748	IMI Commercial	CCI 250	42.0	2494	46.0	2746
Alliant Power Pro Varmint	Federal	Federal 210	39.8	2518	44.2	2744
IMR 4320	IMI Commercial	CCI 200	42.0	2457	46.0 C	2736
Hogdon H414	IMI Commercial	CCI 250	47.0	2425	51.0 C	2732
Winchester 760	IMI Commercial	CCI 250	47.0	2379	51.0 C	2711
IMR 4895	IMI Commercial	CCI 200	39.0	2373	43.0	2705
IMR 4166	Federal	Federal 210	38.3	2431	42.1	2630
Alliant Reloder 10X	IMI Commercial	CCI 200	34.0	2365	38.0	2625
IMR 4350	IMI Commercial	CCI 200	45.0	2334	49.0 C	2600
IMR SR 4759 (reduced load)	IMI Commercial	CCI 200	22.0	1639	24.0	1809

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load