



308 Winchester

.308"	30
	GD
Weight (grains)	150
Ballistic Coefficient	0.503
Sectional Density	0.226
COAL Tested	2.800"
Speer Part No.	308150GDB

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	47.9	2729	53.1 C	3025
Accurate 2520	Federal	Federal 210	43.4	2740	47.9	2957
Hodgdon CFE 223	Federal	Federal 210	46.2	2681	51.2	2951
Alliant Power Pro Varmint	Federal	Federal 210	42.2	2643	46.7	2895
Alliant Reloder 15	Federal	Federal 210	43.2	2622	47.8	2890
Hodgdon Varget	Federal	Federal 210	42.1	2635	46.7 C	2873
IMR 4064	Federal	Federal 210	42.0	2606	46.6 C	2872
Alliant AR-Comp	Federal	Federal 210	40.8	2628	45.1	2868
IMR 4895	Federal	Federal 210	41.7	2588	46.2	2862
Accurate 4064	Federal	Federal 210	43.4	2586	48.0 C	2848
Hodgdon H335	Federal	Federal 210	40.5	2583	44.8	2832
Vihavuori N135	Federal	Federal 210	39.3	2546	43.5	2809

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load