



32 Winchester Special

.321"	32
	SPFN Hot-Cor®
Weight (grains)	170
Ballistic Coefficient	0.283
Sectional Density	0.236
COAL Tested	2.560"
Speer Part No.	2259

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	37.8	2205	42.0 C	2407
Alliant AR-Comp	Federal	Federal 210	31.0	2109	34.2 C	2305
Hodgdon CFE 223	Federal	Federal 210	36.0	2104	39.5 C	2301
IMR 4895	Winchester	CCI 200	33.0	2091	35.0	2238
IMR 3031	Winchester	CCI 200	32.0	2082	34.0	2234
Winchester 748	Winchester	CCI 250	34.0	2086	36.0	2229
Alliant Power Pro Varmint	Federal	Federal 210	31.5	2097	34.2	2229
Alliant Reloder 15	Federal	Federal 210	31.9	2025	35.0	2215
IMR 4064	Winchester	CCI 200	34.0	2060	36.0	2203
Hodgdon BL-C(2)	Winchester	CCI 250	31.0	2040	33.0	2196
IMR 4166	Federal	Federal 210	29.1	1933	32.1	2097
IMR 4320	Winchester	CCI 200	33.5	1958	35.5	2094
IMR 4198	Winchester	CCI 200	23.5	1921	25.5	2086
IMR 4350	Winchester	CCI 200	35.0	1839	37.0	1961
IMR SR 4759 (reduced load)	Winchester	CCI 200	16.0	1523	18.0	1713

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load