



338-06 A-Square

.338"	338
Weight (grains)	Spitzer BTSP
Ballistic Coefficient	225
Sectional Density	0.497
COAL Tested	0.281
Speer Part No.	3.340"
	2406

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 19	Reformed Rem 35 Whelen	CCI 200	60.5	2525	64.5 C	2694
Vihtavuori N160	Reformed Rem 35 Whelen	CCI 200	59.5	2520	63.5 C	2691
Hodgdon H4350	Reformed Rem 35 Whelen	CCI 200	58.0	2512	62.0 C	2687
Alliant Reloder 15	Reformed Rem 35 Whelen	CCI 200	50.5	2474	54.5	2672
IMR 4350	Reformed Rem 35 Whelen	CCI 200	57.0	2495	61.0 C	2671
Winchester 760	Reformed Rem 35 Whelen	CCI 200	57.0	2489	61.0	2666
IMR 4320	Reformed Rem 35 Whelen	CCI 200	50.5	2430	54.5	2625
IMR 4064	Reformed Rem 35 Whelen	CCI 200	49.0	2406	53.0	2606
Vihtavuori N150	Reformed Rem 35 Whelen	CCI 200	50.0	2407	54.0	2603
Accurate 4350	Reformed Rem 35 Whelen	CCI 200	56.0	2319	60.0 C	2580
IMR 4831	Reformed Rem 35 Whelen	CCI 200	57.0	2400	61.0 C	2571
Accurate 3100	Reformed Rem 35 Whelen	CCI 200	59.0	2396	63.0 C	2561

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load