



## 338 Remington Ultra Magnum

<b>.338"</b>	<b>338</b>
	<b>Spitzer SP Hot-</b>
	<b>Cor®</b>
<b>Weight (grains)</b>	200
<b>Ballistic Coefficient</b>	0.426
<b>Sectional Density</b>	0.250
<b>COAL Tested</b>	3.500"
<b>Speer Part No.</b>	2405

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 22	Federal	Federal 215	94.0	3105	<b>98.0</b>	3255
Vihtavuori N560	Federal	Federal 215	93.0	3062	<b>97.0</b>	3223
Alliant Reloder 19	Federal	Federal 215	91.0	3085	<b>95.0</b>	3216
Alliant Reloder 25	Federal	Federal 215	97.0	3060	<b>101.0 C</b>	3193
Hodgdon H4350	Federal	Federal 215	85.0	3043	<b>89.0</b>	3180
IMR 7828	Federal	Federal 215	92.0	3015	<b>96.0</b>	3179
Ramshot Magnum	Federal	Federal 215	101.0	3078	<b>105.0 C</b>	3168
Accurate MagPro	Federal	Federal 215	96.0	2985	<b>100.0</b>	3167
IMR 4350	Federal	Federal 215	84.0	2981	<b>88.0</b>	3151

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*