



338 Ruger Compact Magnum

.338"	338 Spitzer SP Hot- Cor®
Weight (grains)	200
Ballistic Coefficient	0.426
Sectional Density	0.250
COAL Tested	2.820"
Speer Part No.	2405

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Hornady	CCI 250	58.1	2638	64.5 C	2898
Accurate 2700	Hornady	CCI 250	57.9	2663	64.1	2897
Alliant Power Pro 2000-MR	Hornady	CCI 250	55.6	2652	61.5	2889
Ramshot Big Game	Hornady	CCI 250	56.4	2643	62.8	2865
Winchester 760	Hornady	CCI 250	57.3	2632	63.5	2863
Hodgdon 4350	Hornady	CCI 250	58.5	2632	64.7 C	2858
Alliant Reloder 17	Hornady	CCI 250	55.3	2551	61.2	2835
Hodgdon CFE 223	Hornady	CCI 250	52.9	2658	58.5	2827
Alliant Reloder 15	Hornady	CCI 250	52.1	2591	57.7	2826
Vihtavuori N550	Hornady	CCI 250	54.1	2561	59.9	2813
Alliant Power Pro Varmint	Hornady	CCI 250	50.2	2582	55.8	2811
Hodgdon Varget	Hornady	CCI 250	49.9	2593	55.4	2785
IMR 4064	Hornady	CCI 250	50.0	2537	55.5	2782
IMR 4451	Hornady	CCI 250	56.0	2515	62.1 C	2766

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load