



338 Winchester Magnum

.338"

**338
Grand Slam® SP**

Weight (grains)	250
Ballistic Coefficient	0.436
Sectional Density	0.313
COAL Tested	3.300"
Speer Part No.	2408

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	69.0	2506	76.6 C	2764
Alliant Power Pro 4000-MR	Federal	Federal 215	64.7	2467	71.9 C	2693
Alliant Reloder 17	Federal	Federal 215	61.9	2437	68.7 C	2665
Alliant Reloder 19	Winchester	CCI 250	68.0	2478	72.0 C	2664
IMR 4350	Winchester	CCI 250	65.0	2509	69.0	2655
Alliant Reloder 16	Federal	Federal 215	62.7	2465	68.3 C	2655
Alliant Reloder 22	Winchester	CCI 250	69.0	2441	73.0 C	2653
IMR 7828	Winchester	CCI 250	71.0	2480	75.0	2652
Alliant Reloder 23	Federal	Federal 215	66.1	2444	72.4 C	2644
Vihtavuori N165	Winchester	CCI 250	70.0	2439	74.0 C	2637
IMR 4831	Winchester	CCI 250	65.0	2451	69.0	2620
Accurate 3100	Winchester	CCI 250	69.0	2472	73.0 C	2616
Hodgdon H4831SC	Winchester	CCI 250	67.0	2492	71.0 C	2616
Hodgdon H4350	Winchester	CCI 250	64.0	2387	68.0 C	2581
Hodgdon H414	Winchester	CCI 250	62.0	2357	66.0	2548
Hodgdon H1000	Winchester	CCI 250	73.0	2380	77.0 C	2545
Accurate 2700	Winchester	CCI 250	61.0	2394	65.0	2526

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load