



340 Weatherby Magnum

.338"	338
	Spitzer SP Hot-
	Cor®
Weight (grains)	200
Ballistic Coefficient	0.426
Sectional Density	0.250
COAL Tested	3.560"
Speer Part No.	2405

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Federal	Federal 215	70.9	2838	78.7	3104
IMR 4831	Federal	Federal 215	81.0	2923	85.0 C	3073
IMR 4350	Federal	Federal 215	79.0	2907	83.0 C	3058
Alliant Reloder 19	Federal	Federal 215	83.0	2899	87.0 C	3032
Winchester 760	Federal	Federal 215	76.0	2879	80.0	3012
Vihtavuori N540	Federal	Federal 215	71.0	2872	75.0	3006
Hodgdon H4350	Federal	Federal 215	77.0	2854	81.0	3004
Hodgdon H4831SC	Federal	Federal 215	85.0	2881	89.0 C	2989
Alliant Reloder 15	Federal	Federal 215	69.0	2796	73.0	2973
Accurate 4350	Federal	Federal 215	80.0	2821	84.0 C	2962
Ramshot Big Game	Federal	Federal 215	71.0	2776	75.0	2945

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load