



340 Weatherby Magnum

.338"	338
	Spitzer BTSP
Weight (grains)	225
Ballistic Coefficient	0.497
Sectional Density	0.281
COAL Tested	3.670"
Speer Part No.	2406

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	78.0	2709	86.3	3018
Alliant Power Pro 4000-MR	Federal	Federal 215	73.1	2703	81.1	2959
Alliant Reloder 23	Federal	Federal 215	75.5	2690	83.8 C	2951
Alliant Reloder 19	Federal	Federal 215	81.0	2776	85.0 C	2924
IMR 4831	Federal	Federal 215	78.0	2765	82.0	2911
Alliant Reloder 17	Federal	Federal 215	66.9	2664	74.1	2905
Alliant Reloder 22	Federal	Federal 215	83.0	2799	87.0 C	2901
Hodgdon H4350	Federal	Federal 215	75.0	2742	79.0	2892
IMR 4350	Federal	Federal 215	76.0	2738	80.0	2886
Hodgdon H4831SC	Federal	Federal 215	82.0	2755	86.0	2882
Accurate 4350	Federal	Federal 215	77.0	2697	81.0	2864
Winchester 760	Federal	Federal 215	73.0	2728	77.0	2854
Vihtavuori N540	Federal	Federal 215	68.0	2686	72.0	2822
Alliant Reloder 15	Federal	Federal 215	66.0	2653	70.0	2799
Ramshot Big Game	Federal	Federal 215	67.0	2611	71.0	2751

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load