



## 350 Remington Magnum

<b>.358"</b>	<b>35</b>
<b>Weight (grains)</b>	<b>SPFN Hot-Cor®</b>
<b>Ballistic Coefficient</b>	180
<b>Sectional Density</b>	0.236
<b>COAL Tested</b>	0.201
<b>Speer Part No.</b>	2.800"
	2435

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon BL-C(2)	Remington	CCI 250	56.0	2729	<b>60.0</b>	2984
IMR 4064	Remington	CCI 200	58.0	2754	<b>62.0 C</b>	2955
IMR 4895	Remington	CCI 200	56.0	2732	<b>60.0</b>	2940
IMR 4320	Remington	CCI 200	57.0	2630	<b>61.0 C</b>	2822
Winchester 748	Remington	CCI 250	58.0	2486	<b>62.0</b>	2711
Hodgdon H380	Remington	CCI 250	58.0	2486	<b>62.0 C</b>	2666
Alliant Reloder 7	Remington	CCI 200	47.0	2349	<b>51.0</b>	2603
Winchester 760	Remington	CCI 250	61.0	2222	<b>65.0 C</b>	2445
IMR SR 4759 (reduced load)	Remington	CCI 200	26.0	1788	<b>28.0</b>	1934

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*