



350 Remington Magnum

.358"	35
Weight (grains)	SPFN Hot-Cor®
Ballistic Coefficient	220
Sectional Density	0.286
COAL Tested	0.245
Speer Part No.	2.740"
	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon BL-C(2)	Remington	CCI 250	56.0	2522	60.0	2708
Winchester 748	Remington	CCI 250	58.0	2515	62.0	2696
IMR 4895	Remington	CCI 200	56.0	2552	60.0	2686
IMR 3031	Remington	CCI 200	55.0	2475	59.0	2673
IMR 4320	Remington	CCI 200	56.0	2471	60.0 C	2660
Hodgdon H322	Remington	CCI 200	51.0	2452	55.0 C	2591
Hodgdon H380	Remington	CCI 250	58.0	2430	62.0 C	2522
Winchester 760	Remington	CCI 250	61.0	2320	65.0 C	2496
Alliant Reloder 7	Remington	CCI 200	45.5	2258	49.5	2450

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load