



350 Remington Magnum

.358"	35
	Spitzer SP Hot-
	Cor®
Weight (grains)	250
Ballistic Coefficient	0.422
Sectional Density	0.279
COAL Tested	2.800"
Speer Part No.	2453

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 748	Remington	CCI 250	53.0	2284	57.0 C	2510
IMR 3031	Remington	CCI 200	48.0	2204	52.0 C	2404
IMR 4895	Remington	CCI 200	49.0	2174	53.0 C	2374
IMR 4064	Remington	CCI 200	51.0	2185	55.0 C	2369
Winchester 760	Remington	CCI 250	54.0	2130	58.0 C	2313
Hodgdon BL-C(2)	Remington	CCI 250	48.0	2085	52.0	2275
IMR 4320	Remington	CCI 200	50.0	2065	54.0 C	2236
Hodgdon H380	Remington	CCI 250	54.0	2029	58.0 C	2185
IMR SR 4759 (reduced load)	Remington	CCI 200	28.0	1681	30.0	1804

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load