



## 356 Winchester

<b>.358"</b>	<b>35 SPFN Hot-Cor®</b>
<b>Weight (grains)</b>	180
<b>Ballistic Coefficient</b>	0.236
<b>Sectional Density</b>	0.201
<b>COAL Tested</b>	2.550"
<b>Speer Part No.</b>	2435

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2015	Winchester	CCI 200	43.0	2361	<b>47.0 C</b>	2717
IMR 8208 XBR	Winchester	CCI 200	44.5	2445	<b>48.5</b>	2644
Vihtavuori N133	Winchester	CCI 200	42.0	2396	<b>46.0 C</b>	2634
Hodgdon H322	Winchester	CCI 200	44.0	2350	<b>48.0</b>	2626
Hodgdon H335	Winchester	CCI 250	44.0	2322	<b>48.0</b>	2554
IMR 4064	Winchester	CCI 200	46.0	2358	<b>50.0</b>	2520
Hodgdon BL-C(2)	Winchester	CCI 250	47.0	2304	<b>51.0 C</b>	2516
IMR 4166	Winchester	CCI 200	43.5	2322	<b>47.9</b>	2509
IMR 4895	Winchester	CCI 200	45.0	2200	<b>49.0</b>	2449
IMR 3031	Winchester	CCI 200	42.0	2179	<b>46.0</b>	2440
Alliant Reloder 7	Winchester	CCI 200	36.0	2121	<b>40.0</b>	2401
Winchester 748	Winchester	CCI 250	47.0	2206	<b>51.0</b>	2393
IMR 4320	Winchester	CCI 200	43.0	2211	<b>47.0</b>	2369

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*