



356 Winchester

.358"

35
SPFN Hot-Cor®

Weight (grains)	220
Ballistic Coefficient	0.286
Sectional Density	0.245
COAL Tested	2.550"
Speer Part No.	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant AR-Comp	Winchester	CCI 200	39.0	2173	44.0	2389
Accurate 2015	Winchester	CCI 200	38.0	2141	42.0 C	2386
Alliant Power Pro Varmint	Winchester	CCI 200	42.5	2234	46.4	2381
Winchester 748	Winchester	CCI 250	45.5	2172	49.5	2369
Vihtavuori N135	Winchester	CCI 200	41.0	2156	45.0 C	2345
IMR 4064	Winchester	CCI 200	42.0	2046	46.0	2340
IMR 4166	Winchester	CCI 200	40.5	2193	43.8	2339
Hodgdon H322	Winchester	CCI 200	39.0	2144	43.0	2323
IMR 4320	Winchester	CCI 200	42.0	2125	46.0	2310
Hodgdon H335	Winchester	CCI 250	39.0	2063	43.0	2294
IMR 4895	Winchester	CCI 200	42.0	2006	46.0	2278
Hodgdon BL-C(2)	Winchester	CCI 250	42.0	2054	46.0 C	2277
Hodgdon H380	Winchester	CCI 250	46.0	1992	50.0 C	2143
Alliant Reloder 7	Winchester	CCI 200	31.0	1877	35.0	2116

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load