



357 Magnum (Rifle)

.357"	38 GDHP	38 JHP
Weight (grains)	125	125
Ballistic Coefficient	0.14	0.129
Sectional Density	0.140	0.140
COAL Tested	1.580"	1.575"
Speer Part No.	4012	4013

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Speer	CCI 550	18.0	1946	20.0 C	2167
Winchester 296	Speer	CCI 550	18.3	1963	20.3 C	2167
Vihtavuori N110	Speer	CCI 500	16.8	1967	17.8	2076
Alliant 2400	Speer	CCI 500	16.5	1868	17.5	2051
Accurate No. 7	Speer	CCI 500	12.0	1583	13.5	1780

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load