



speer
bullets

358 Norma Magnum

.358"	35
	SPFN Hot-Cor®
Weight (grains)	180
Ballistic Coefficient	0.236
Sectional Density	0.201
COAL Tested	3.340"
Speer Part No.	2435

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4895	Norma	CCI 250	65.0	2943	69.0	3133
IMR 4320	Norma	CCI 250	68.0	2945	72.0	3132
IMR 4064	Norma	CCI 250	67.0	2933	71.0	3124
Hodgdon H380	Norma	CCI 250	68.0	2910	72.0	3075
IMR 4350	Norma	CCI 250	74.0	2778	78.0	2948
Hodgdon H414	Norma	CCI 250	73.0	2652	77.0	2836
IMR SR 4759 (reduced load)	Norma	CCI 250	30.0	1893	32.0	2013

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load