



358 Winchester

.358"	35
	Spitzer SP Hot-
	Cor®
Weight (grains)	250
Ballistic Coefficient	0.422
Sectional Density	0.279
COAL Tested	2.775"
Speer Part No.	2453

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H335	Winchester	CCI 250	41.0	2133	45.0	2354
Accurate 2015	Winchester	CCI 200	39.0	2155	43.0	2334
Vihtavuori N135	Winchester	CCI 200	42.0	2141	46.0 C	2321
Hodgdon H322	Winchester	CCI 200	39.0	2065	43.0	2308
Alliant Power Pro Varmint	Hornady	CCI 200	42.0	2120	46.4	2298
IMR 4064	Winchester	CCI 200	40.0	2050	44.0	2282
Hodgdon BL-C(2)	Winchester	CCI 250	43.0	2081	47.0 C	2279
Winchester 748	Winchester	CCI 250	43.0	2042	47.0	2273
IMR 4320	Winchester	CCI 200	40.0	2017	44.0	2259
IMR 3031	Winchester	CCI 200	38.0	2021	42.0	2258
Hodgdon Benchmark	Hornady	CCI 200	40.0	2118	43.3	2242
IMR 8208	Hornady	CCI 200	40.0	2063	43.6	2240
Alliant Reloder 7	Winchester	CCI 200	33.0	1927	37.0	2184

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load