



## 35 Remington (Rifle)

.358"	35
Weight (grains)	SPFN Hot-Cor® 220
Ballistic Coefficient	0.286
Sectional Density	0.245
COAL Tested	2.470"
Speer Part No.	2439

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 2000-MR	Federal	Federal 210	38.0	1920	<b>41.2 C</b>	2031
Alliant AR-Comp	Federal	Federal 210	30.2	1780	<b>33.0</b>	1925
Accurate 2015	Winchester	CCI 200	29.0	1666	<b>33.0</b>	1915
Hodgdon CFE 223	Federal	Federal 210	32.9	1797	<b>35.3</b>	1901
IMR 4064	Winchester	CCI 200	32.0	1641	<b>36.0</b>	1851
Hodgdon H414	Winchester	CCI 250	36.0	1656	<b>40.0</b>	1841
Winchester 748	Winchester	CCI 250	31.0	1675	<b>35.0</b>	1840
IMR 8208 XBR	Federal	Federal 210	29.0	1647	<b>32.1</b>	1840
Alliant Reloder 15	Federal	Federal 210	31.4	1643	<b>34.9</b>	1824
Alliant Power Pro Varmint	Federal	Federal 210	29.7	1650	<b>32.6</b>	1822
Vihtavuori N133	Winchester	CCI 200	27.0	1591	<b>31.0</b>	1816
Hodgdon BL-C(2)	Winchester	CCI 250	31.0	1552	<b>35.0</b>	1802
IMR 4895	Winchester	CCI 200	31.5	1640	<b>35.5</b>	1797
Hodgdon H335	Winchester	CCI 250	28.0	1467	<b>32.0</b>	1792
IMR 3031	Winchester	CCI 200	29.5	1525	<b>33.5</b>	1788
IMR 4320	Winchester	CCI 200	29.0	1494	<b>33.0</b>	1694
Alliant Reloder 7	Winchester	CCI 200	20.5	1149	<b>24.5</b>	1530

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*