



## 375 Holland &amp; Holland Magnum

<b>.375"</b>	<b>375</b>
	<b>Semi-Spitzer SP</b>
	<b>Hot-Cor®</b>
<b>Weight (grains)</b>	235
<b>Ballistic Coefficient</b>	0.301
<b>Sectional Density</b>	0.239
<b>COAL Tested</b>	3.600"
<b>Speer Part No.</b>	2471

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon CFE 223	Federal	CCI 250	71.0	2797	<b>78.7</b>	2969
Vihtavuori N540	Winchester	CCI 250	70.0	2835	<b>74.0</b>	2948
Hodgdon H380	Winchester	CCI 250	80.0	2826	<b>84.0</b>	2930
Alliant Reloder 15	Winchester	CCI 250	74.0	2828	<b>78.0</b>	2920
IMR 8208	Federal	CCI 250	67.0	2755	<b>72.0</b>	2901
IMR 4166	Federal	CCI 250	65.5	2707	<b>72.0</b>	2882
Accurate 4350	Winchester	CCI 250	81.0	2738	<b>85.0 C</b>	2877
Vihtavuori N140	Winchester	CCI 250	71.0	2766	<b>75.0</b>	2873
IMR 4064	Winchester	CCI 250	70.0	2707	<b>74.0</b>	2854
IMR 4350	Winchester	CCI 250	81.0	2672	<b>85.0 C</b>	2840
Hodgdon H414	Winchester	CCI 250	84.0	2736	<b>86.0 C</b>	2808
Hodgdon Varget	Winchester	CCI 250	70.0	2686	<b>74.0</b>	2803
Hodgdon H4350	Winchester	CCI 250	78.0	2715	<b>82.0 C</b>	2799
Accurate 2700	Winchester	CCI 250	74.0	2647	<b>78.0</b>	2778
IMR 3031	Winchester	CCI 250	63.0	2478	<b>67.0</b>	2702
IMR 4895	Winchester	CCI 250	64.0	2420	<b>68.0</b>	2591
IMR SR 4759 (reduced load)	Winchester	CCI 250	28.0	1610	<b>30.0</b>	1701

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*