



speer
bullets

375 Ruger

.375"	375
	Semi-Spitzer SP
	Hot-Cor®
Weight (grains)	235
Ballistic Coefficient	0.301
Sectional Density	0.239
COAL Tested	3.310"
Speer Part No.	2471

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 17	Hornady	CCI 250	80.4	2871	89.0	3177
Hodgdon H4350	Hornady	CCI 250	83.1	2886	93.4	3174
Ramshot Big Game	Hornady	CCI 250	80.7	2937	89.5	3160
Alliant Reloder 16	Hornady	CCI 250	82.2	2898	91.0	3154
Winchester 760	Hornady	CCI 250	81.2	2908	89.9	3140
Alliant Reloder 15	Hornady	CCI 250	75.1	2882	83.3	3125
IMR 4451	Hornady	CCI 250	81.9	2839	90.9	3107
Alliant Power Pro 2000-MR	Hornady	CCI 250	76.3	2977	82.0	3094
Alliant Power Pro Varmint	Hornady	CCI 250	72.4	2857	80.4	3089
Hodgdon Varget	Hornady	CCI 250	75.9	2961	80.4	3088
IMR 4895	Hornady	CCI 250	72.1	2823	80.0	3078
Alliant AR-Comp	Hornady	CCI 250	68.5	2837	74.5	2983

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load