



375 Ruger

.375"	375
Weight (grains)	Spitzer BTSP 270
Ballistic Coefficient	0.478
Sectional Density	0.274
COAL Tested	3.320"
Speer Part No.	2472

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 16	Hornady	CCI 250	78.8	2752	86.8 C	3005
Hodgdon H4350	Hornady	CCI 250	78.8	2714	87.3 C	2966
Alliant Reloder 17	Hornady	CCI 250	74.6	2665	82.9 C	2965
Ramshot Big Game	Hornady	CCI 250	75.8	2745	84.1	2944
Alliant Power Pro 2000-MR	Hornady	CCI 250	73.8	2695	81.5	2933
Alliant Power Pro 4000-MR	Hornady	CCI 250	79.3	2692	88.0 C	2927
Winchester 760	Hornady	CCI 250	73.4	2631	81.4	2893
Alliant Reloder 15	Hornady	CCI 250	69.4	2632	76.9	2886
IMR 4451	Hornady	CCI 250	77.3	2637	85.3 C	2885
Hodgdon Varget	Hornady	CCI 250	68.7	2659	76.0	2870
Alliant Power Pro Varmint	Hornady	CCI 250	66.6	2610	73.8	2836

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load