



375 Winchester

.375"	375
	Semi-Spitzer SP
	Hot-Cor®
Weight (grains)	235
Ballistic Coefficient	0.301
Sectional Density	0.239
COAL Tested	2.560"
Speer Part No.	2471

not suitable for use in tubular magazines.

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Winchester	CCI 200	31.0	1819	35.0 C	2091
IMR 4198	Winchester	CCI 200	28.0	1731	32.0	2006
Accurate 2015	Winchester	CCI 200	32.0	1747	36.0 C	1994
Vihtavuori N133	Winchester	CCI 200	33.0	1745	37.0 C	1981
IMR 4895	Winchester	CCI 200	32.0	1576	36.0 C	1949
Accurate 2230	Winchester	CCI 200	33.5	1725	37.5 C	1926
Hodgdon H322	Winchester	CCI 200	31.0	1663	35.0	1862
IMR 3031	Winchester	CCI 200	31.0	1530	35.0 C	1786

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load