



speer®
bullets

416 Rigby

.416"

416
Mag-Tip SP Hot-
Cor®

Weight (grains)	350
Ballistic Coefficient	0.332
Sectional Density	0.289
COAL Tested	3.630"
Speer Part No.	2477

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	98.3	2434	108.8	2747
Alliant Reloder 16	Federal	Federal 215	89.9	2475	98.9	2711
Alliant Power Pro 4000-MR	Federal	Federal 215	91.9	2484	101.2	2698
Alliant Reloder 23	Federal	Federal 215	95.1	2430	105.1 C	2687
Alliant Reloder 17	Federal	Federal 215	85.8	2479	95.0	2681
IMR 7977	Federal	Federal 215	100.4	2369	111.0 C	2631
IMR 4831	Federal	CCI 250	98.0	2441	102.0	2577
IMR 4350	Federal	CCI 250	95.0	2424	99.0	2560
Alliant Reloder 19	Federal	CCI 250	101.0	2438	105.0	2560
Hodgdon H4831SC	Federal	CCI 250	103.0	2457	107.0	2555
Accurate 3100	Federal	CCI 250	101.0	2395	105.0	2524
IMR 7828	Federal	CCI 250	101.0	2379	105.0	2510

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load