



444 Marlin

.429"	44 DCHP	44 DCSP
Weight (grains)	240	240
Ballistic Coefficient	0.175	0.175
Sectional Density	0.186	0.186
COAL Tested	2.540"	2.545"
Speer Part No.	4455	4456

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 7	Remington	CCI 200	46.0	2184	50.0	2354
Alliant Reloder 10X	Remington	CCI 200	49.0	2152	53.0	2348
Vihtavuori N133	Remington	CCI 200	54.0	2184	56.0 C	2319
IMR 8208 XBR	Hornady	CCI 200	54.5	2185	57.5 C	2313
Hodgdon H322	Remington	CCI 200	50.0	2107	54.0 C	2307
Hodgdon BENCHMARK	Remington	CCI 200	50.0	2065	54.0 C	2267
IMR 4198	Remington	CCI 200	40.0	2079	44.0	2245
Accurate 2015	Remington	CCI 200	50.0	2048	54.0	2240
Ramshot X-Terminator	Remington	CCI 250	49.0	2021	53.0	2165
Accurate 5744	Remington	CCI 200	33.0	1833	37.0	2032

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load