



44 Remington Magnum (Rifle)

.429"	44
Weight (grains)	DCSP
Ballistic Coefficient	270
Sectional Density	0.193
COAL Tested	0.210
COAL Tested	1.595"
Speer Part No.	4461

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Hodgdon H110	Winchester	CCI 350	19.0	1458	21.0	1569
Hodgdon Lil' Gun	Winchester	CCI 350	17.5	1445	19.5	1552
Winchester 296	Winchester	CCI 350	18.5	1406	20.5	1546
Ramshot Enforcer	Winchester	CCI 350	17.0	1338	19.0	1512
Vihtavuori N110	Winchester	CCI 300	16.0	1348	18.0	1463
Accurate 1680	Winchester	CCI 350	22.5	1272	24.5 C	1375
Accurate No. 9	Winchester	CCI 300	14.0	1159	16.0	1359
Alliant 2400	Winchester	CCI 300	15.5	1211	17.5	1352
IMR 4227	Winchester	CCI 300	18.5	1231	20.5	1350

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load