



45-70 Government (Lever Actions)

.458"	45
	JHP
Weight (grains)	300
Ballistic Coefficient	0.206
Sectional Density	0.204
COAL Tested	2.530"
Speer Part No.	2482

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 8208	Winchester	CCI 200	59.5	1927	63.4	2115
Hodgdon BENCHMARK	Winchester	CCI 200	58.0	1915	62.4	2114
Alliant Reloder 7	Winchester	CCI 200	43.0	1852	47.0	2011
Hodgdon H4895	Winchester	CCI 200	58.0	1739	62.0	1987
IMR 4166	Winchester	CCI 200	53.0	1783	59.0	1982
Hodgdon Varget	Winchester	CCI 200	57.0	1794	61.0	1976
Alliant Reloder 10X	Winchester	CCI 200	48.0	1837	52.0	1973
Hodgdon H322	Winchester	CCI 200	52.0	1675	56.0	1951
IMR 4895	Winchester	CCI 200	57.0	1723	61.0	1924
IMR 3031	Winchester	CCI 200	55.0	1690	59.0	1918
Vihtavuori N133	Winchester	CCI 200	50.0	1692	54.0	1915
IMR 4064	Winchester	CCI 200	57.0	1733	61.0	1908
XMR 2015	Winchester	CCI 200	51.0	1706	55.0	1878
IMR 4320	Winchester	CCI 200	55.0	1581	59.0	1827
IMR 4198	Winchester	CCI 200	39.0	1609	43.0	1765
XMP 5744	Winchester	CCI 200	36.0	1559	40.0	1745
IMR SR 4759	Winchester	CCI 200	29.0	1481	31.0	1603

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load