



45-70 Government (Strong Actions)

.458"	45
	JHP
Weight (grains)	300
Ballistic Coefficient	0.206
Sectional Density	0.204
COAL Tested	2.530"
Speer Part No.	2482

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihtavuori N133	Winchester	CCI 200	56.0	1982	60.0	2202
Alliant Reloder 10X	Winchester	CCI 200	53.0	2015	57.0	2167
Hodgdon H322	Winchester	CCI 200	57.0	1929	61.0 C	2145
Hodgdon BENCHMARK	Winchester	CCI 200	57.0	1912	61.0	2139
Accurate 2015	Winchester	CCI 200	57.0	1930	61.0	2120
Hodgdon H4895	Winchester	CCI 200	62.0	2006	64.0 C	2115
Hodgdon Varget	Winchester	CCI 200	63.0	2018	65.0 C	2087
IMR 4895	Winchester	CCI 200	62.0	1961	64.0 C	2060
Alliant Reloder 7	Winchester	CCI 200	50.0	1873	54.0	2050
IMR 4320	Winchester	CCI 200	61.0	1909	65.0 C	2048
IMR 4198	Winchester	CCI 200	44.0	1817	48.0	2037
IMR 3031	Winchester	CCI 200	59.0	1929	61.0 C	2023
IMR 4064	Winchester	CCI 200	61.0	1891	63.0 C	2002

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load