



450 Marlin

.458"	45
	JHP
Weight (grains)	300
Ballistic Coefficient	0.206
Sectional Density	0.204
COAL Tested	2.525"
Speer Part No.	2482

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro 1200-R	Hornady	CCI 200	59.5	2391	63.5 C	2547
Hodgdon H322	Hornady	CCI 200	57.0	2228	61.0 C	2405
Alliant Reloder 7	Hornady	CCI 200	52.0	2220	56.0 C	2392
Vihtavuori N133	Hornady	CCI 200	55.0	2206	59.0 C	2366
Hodgdon BENCHMARK	Hornady	CCI 200	58.0	2229	62.0 C	2364
Vihtavuori N120	Hornady	CCI 200	49.0	2182	53.0	2359
IMR 4198	Hornady	CCI 200	46.0	2177	50.0	2353
Accurate 2230	Hornady	CCI 250	55.0	2234	59.0	2333
Accurate 2015	Hornady	CCI 200	56.0	2132	60.0 C	2303
Hodgdon H4227	Hornady	CCI 200	40.0	2017	44.0	2184
IMR 4895	Hornady	CCI 200	60.0C	2093	62.0 C	2184
Accurate 5744	Hornady	CCI 200	36.0	1808	40.0	1996

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load