



458 Lott

<b>.458"</b>	<b>45</b>
	<b>SPFN Hot-Cor®</b>
<b>Weight (grains)</b>	350
<b>Ballistic Coefficient</b>	0.218
<b>Sectional Density</b>	0.238
<b>COAL Tested</b>	3.400"
<b>Speer Part No.</b>	2478

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Power Pro Varmint	Norma	Federal 215	96.0	2765	<b>102.0 C</b>	2868
Accurate 2460	Norma	Federal 215	88.5	2674	<b>98.0 C</b>	2865
Accurate LT-32	Norma	Federal 215	82.5	2580	<b>90.0 C</b>	2768
Hodgdon H322	Hornady	Federal 215	86.0	2708	<b>88.0 C</b>	2749
Vihtavuori N130	Norma	Federal 215	77.7	2566	<b>85.7 C</b>	2739
Alliant Power Pro 1200-R	Norma	Federal 215	73.5	2552	<b>81.5</b>	2728
Ramshot TAC	Hornady	Federal 215	91.0	2676	<b>93.0 C</b>	2715
Hodgdon BENCHMARK	Hornady	Federal 215	87.0	2672	<b>89.0 C</b>	2714
Alliant Reloder 10X	Hornady	Federal 215	82.0	2662	<b>84.0 C</b>	2712
Alliant Reloder 7	Hornady	Federal 215	79.0	2650	<b>81.0</b>	2699
IMR 4198	Hornady	Federal 215	78.0	2645	<b>80.0 C</b>	2693
Accurate 2015	Hornady	Federal 215	83.0	2562	<b>85.0 C</b>	2603
Vihtavuori N133	Hornady	Federal 215	83.0	2534	<b>85.0 C</b>	2588

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*