



## 458 Winchester Magnum

.458"	45
Weight (grains)	400
Ballistic Coefficient	0.259
Sectional Density	0.272
COAL Tested	3.115"
Speer Part No.	2479

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Accurate 2230	Winchester	CCI 250	78.0	2290	82.0 C	2429
Hodgdon BL-C(2)	Winchester	CCI 250	75.0	2269	79.0 C	2410
IMR 8208	Federal	CCI 250	76.0	2300	80.2 C	2410
Hodgdon BENCHMARK	Federal	CCI 250	75.0	2283	79.4 C	2402
Accurate 2015 BR	Winchester	CCI 250	70.0	2269	74.0 C	2386
Alliant Power Pro 1200-R	Federal	CCI 250	70.5	2270	74.1	2381
Alliant Reloder 7	Winchester	CCI 250	70.0	2190	74.0	2316
Vihtavuori N133	Winchester	CCI 250	70.0	2174	74.0 C	2305
Hodgdon H4198	Winchester	CCI 250	60.0	2107	64.0	2231
IMR 3031	Winchester	CCI 250	67.0	2055	71.0 C	2169
IMR SR 4759	Winchester	CCI 250	26.0	1262	30.0	1445

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*