



6.5X55mm Swedish Mauser (Military Actions)

.264"	6.5mm
	Spitzer SP Hot-
	Cor®
Weight (grains)	140
Ballistic Coefficient	0.498
Sectional Density	0.287
COAL Tested	3.000"
Speer Part No.	1441

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 210	37.7	2371	41.5	2534
Alliant Reloder 17	Federal	Federal 210	35.0	2309	38.6	2490
Alliant Power Pro 4000-MR	Federal	Federal 210	36.6	2368	38.7	2462
Alliant Reloder 22	Remington	CCI 200	38.0	2382	40.0	2461
Alliant Reloder 23	Federal	Federal 210	35.6	2293	39.3	2450
Alliant Reloder 19	Remington	CCI 200	38.0	2312	40.0	2399
Hodgdon H4831SC	Remington	CCI 200	37.0	2288	39.0	2379
Hodgdon H4350	Remington	CCI 200	34.0	2257	36.0	2350
IMR 4831	Remington	CCI 200	34.0	2254	36.0	2339
IMR 4350	Remington	CCI 200	34.0	2254	36.0	2337
Alliant Reloder 16	Federal	Federal 210	34.0	2330	34.0	2330
IMR 4064	Remington	CCI 200	31.0	3193	33.0	2300
Hodgdon Varget	Remington	CCI 200	31.0	2165	33.0	2276

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load