



7mm-08 Remington

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	2.800"	2.800"	2.760"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Winchester 760	Remington	CCI 250	41.0	2475	45.0 C	2735
Alliant Reloder 19	Remington	CCI 200	43.0	2456	47.0 C	2710
Alliant Power Pro 4000-MR	Federal	Federal 210	44.0 C	2547	47.0 C	2706
Hodgdon H414	Remington	CCI 250	41.0	2474	45.0 C	2704
Alliant Reloder 17	Federal	Federal 210	40.0	2400	44.4 C	2682
Accurate 4350	Remington	CCI 200	42.0	2484	46.0 C	2671
Alliant Reloder 16	Federal	Federal 210	40.8 C	2462	45.0 C	2670
IMR 4350	Remington	CCI 200	41.0	2463	45.0 C	2666
Accurate 2520	Remington	CCI 250	36.0	2425	40.0	2659
Vihavuori N165	Remington	CCI 200	45.0	2415	49.0 C	2654
Alliant Power Pro 2000-MR	Federal	Federal 210	37.9	2412	42.1	2652
Ramshot Big Game	Federal	Federal 210	38.6	2413	42.7	2632
IMR 4831	Remington	CCI 200	42.0	2406	46.0 C	2615
Hodgdon H4350	Remington	CCI 200	41.0	2423	45.0 C	2611
Hodgdon H4831SC	Remington	CCI 200	46.0	2512	48.0 C	2598
Alliant Reloder 15	Remington	CCI 200	34.0	2343	38.0	2506
Winchester 748	Remington	CCI 250	35.0	2315	39.0	2503
Hodgdon H380	Remington	CCI 250	38.0	2281	42.0	2502

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load