



## 7mm Remington Magnum

<b>.284"</b>	<b>7mm</b>
	<b>TNT® HP</b>
<b>Weight (grains)</b>	110
<b>Ballistic Coefficient</b>	0.384
<b>Sectional Density</b>	0.195
<b>COAL Tested</b>	3.250"
<b>Speer Part No.</b>	1616

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 22	Remington	CCI 250	71.0	3265	<b>75.0 C</b>	3503
Alliant Reloder 19	Remington	CCI 250	70.0	3237	<b>74.0 C</b>	3489
Alliant Reloder 16	Federal	Federal 215	58.9	3180	<b>65.2</b>	3485
Vihtavuori N165	Remington	CCI 250	73.0	3275	<b>77.0 C</b>	3481
Hodgdon H4350	Remington	CCI 250	67.0	3227	<b>71.0 C</b>	3451
Accurate 4350	Remington	CCI 250	67.0	3255	<b>71.0</b>	3427
IMR 4831	Remington	CCI 250	67.0	3208	<b>71.0</b>	3412
IMR 4350	Remington	CCI 250	62.0	3211	<b>66.0</b>	3379
Accurate 3100	Remington	CCI 250	69.0	3160	<b>73.0 C</b>	3358
Hodgdon H4831SC	Remington	CCI 250	68.0	3174	<b>72.0</b>	3348
Winchester 760	Remington	CCI 250	61.0	3117	<b>65.0</b>	3323
Alliant Reloder 15	Remington	CCI 250	54.0	3034	<b>58.0</b>	3256

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*