



7mm Remington Short Action Ultra Magnum

.284"	7mm Spitzer SP Hot- Cor®	7mm Spitzer BTSP
Weight (grains)	130	130
Ballistic Coefficient	0.368	0.424
Sectional Density	0.230	0.230
COAL Tested	2.785"	2.785"
Speer Part No.	1623	1624

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4831	Remington	CCI 200	58.0	3042	62.0	3231
Alliant Reloder 19	Remington	CCI 200	61.0	3051	65.0	3229
Vihtavuori N165	Remington	CCI 200	62.0	3106	66.0 C	3229
Alliant Reloder 22	Remington	CCI 200	61.0	3051	65.0	3214
Winchester 760	Remington	CCI 250	56.0	3032	60.0	3186
IMR 4350	Remington	CCI 200	55.0	3003	59.0	3173
Hodgdon H4831SC	Remington	CCI 200	59.0	2952	63.0	3112
Alliant Reloder 15	Remington	CCI 200	48.0	2924	52.0	3085

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load