



## 7mm Remington Short Action Ultra Magnum

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.257	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.785"	2.785"	2.750"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihavuori N560	Remington	CCI 200	59.0	2876	<b>63.0</b>	3085
Alliant Reloder 22	Remington	CCI 200	59.0	2901	<b>63.0</b>	3061
IMR 4831	Remington	CCI 200	56.0	2872	<b>60.0</b>	3051
Alliant Reloder 19	Remington	CCI 200	58.0	2869	<b>62.0</b>	3040
IMR 4350	Remington	CCI 200	53.0	2816	<b>57.0</b>	3006
Winchester 760	Remington	CCI 250	54.0	2831	<b>58.0</b>	3004
Hodgdon H4831SC	Remington	CCI 200	57.0	2830	<b>61.0</b>	2984
Hodgdon H4350	Remington	CCI 200	52.0	2806	<b>56.0</b>	2981
Accurate 5744 (reduced load)	Remington	CCI 200	26.0	1914	<b>28.0</b>	2045

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*