



7mm Remington Ultra Magnum

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	160	160	160
Ballistic Coefficient	0.519	0.504	0.389
Sectional Density	0.283	0.283	0.283
COAL Tested	3.600"	3.600"	3.580"
Speer Part No.	1634	1635	1638

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Vihavuori N560	Remington	Federal 215	87.0	3145	91.0	3311
Hodgdon US 869	Remington	Federal 215	101.0	3075	105.0	3237
Hodgdon Retumbo	Remington	Federal 215	91.0	3031	95.0	3219
Accurate 8700	Remington	Federal 215	99.0	3054	103.0	3198
Alliant Reloder 22	Remington	Federal 215	83.0	3014	87.0	3177
Alliant Reloder 25	Remington	Federal 215	87.0	3005	91.0	3174
Ramshot Magnum	Remington	Federal 215	88.0	3016	92.0	3169
IMR 7828	Remington	Federal 215	83.0	2984	87.0	3149
Alliant Reloder 19	Remington	Federal 215	81.0	2928	85.0	3132

WARNING: Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

Maximum loads should be used with CAUTION • C = Compressed Load