



## 7mm Winchester Short Magnum

.284"	7mm Spitzer BTSP	7mm Spitzer SP Hot-Cor®	7mm Grand Slam® SP/CANN
Weight (grains)	145	145	145
Ballistic Coefficient	0.472	0.416	0.353
Sectional Density	0.257	0.257	0.257
COAL Tested	2.780"	2.780"	2.745"
Speer Part No.	1628	1629	1632

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
Alliant Reloder 26	Federal	Federal 215	60.9	2932	<b>67.3</b>	3185
Alliant Power Pro 4000-MR	Federal	Federal 215	58.4	2876	<b>64.6</b>	3143
Alliant Reloder 23	Federal	Federal 215	59.8	2886	<b>66.4 C</b>	3139
Alliant Reloder 17	Federal	Federal 215	56.0	2904	<b>62.0</b>	3139
Alliant Reloder 16	Federal	Federal 215	55.2	2852	<b>61.1</b>	3084
Alliant Reloder 22	Winchester	CCI 200	62.0	2927	<b>66.0</b>	3079
Alliant Reloder 19	Winchester	CCI 200	61.0	2893	<b>65.0</b>	3063
Accurate 3100	Winchester	CCI 200	62.0	2898	<b>66.0</b>	3052
IMR 4831	Winchester	CCI 200	58.0	2878	<b>62.0</b>	3047
IMR 4350	Winchester	CCI 200	56.0	2851	<b>60.0</b>	3027
Hodgdon H4350	Winchester	CCI 200	54.0	2818	<b>58.0</b>	2990
Hodgdon H4831SC	Winchester	CCI 200	59.0	2839	<b>63.0</b>	2986
Vihavuori N160	Winchester	CCI 200	55.0	2814	<b>59.0</b>	2933
Accurate 5744 (reduced load)	Winchester	CCI 200	28.0	1959	<b>30.0</b>	2084

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*