



## 8mm Mauser (8x57mm)

<b>.323"</b>	<b>8mm</b>
	<b>Semi Spitzer SP</b>
	<b>Hot-Cor®</b>
<b>Weight (grains)</b>	170
<b>Ballistic Coefficient</b>	0.311
<b>Sectional Density</b>	0.233
<b>COAL Tested</b>	2.890"
<b>Speer Part No.</b>	2283

Propellant	Case	Primer	START CHARGE		MAXIMUM CHARGE	
			Weight (grains)	Muzzle Velocity (feet/sec)	Weight (grains)	Muzzle Velocity (feet/sec)
IMR 4064	Remington	CCI 200	45.0	2509	<b>49.0</b>	2723
Winchester 748	Remington	CCI 250	50.0	2451	<b>54.0</b>	2716
IMR 4895	Remington	CCI 200	42.0	2401	<b>46.0</b>	2640
Alliant Reloder 15	Remington	CCI 200	45.0	2425	<b>49.0</b>	2632
IMR 4350	Remington	CCI 200	51.0	2429	<b>55.0 C</b>	2632
IMR 3031	Remington	CCI 200	40.0	2356	<b>44.0</b>	2600
Hodgdon H380	Remington	CCI 250	50.0	2359	<b>54.0</b>	2588
Vihtavuori N140	Remington	CCI 200	44.0	2378	<b>48.0</b>	2574
Hodgdon H335	Remington	CCI 250	42.0	2262	<b>46.0</b>	2525
Accurate 2700	Remington	CCI 250	45.0	2266	<b>49.0</b>	2486
Accurate 4350	Remington	CCI 200	49.0	2185	<b>53.0 C</b>	2368
Hodgdon H322	Remington	CCI 200	38.0	2049	<b>42.0</b>	2324
IMR 4198(reduced load)	Remington	CCI 200	25.0	1778	<b>27.0</b>	1914

**WARNING:** Improper handloading practices can result in serious personal injury and/or property damage. Refer to the current SPEER® Reloading Manual for handloading instructions. Be thoroughly familiar with those instructions before using these loads. As Vista Outdoor Operations LLC has no control over individual handloading practices or the condition of firearms in which the resulting ammo may be used, we disclaim all liability for any damages that may result from the use of this information.

*Maximum loads should be used with CAUTION • C = Compressed Load*